



IP54

DEHUMIDIFIERS



IP54

Special Features

- Condensate pump factory equipped
- Hour meter factory equipped
- IP54 class rating



Standard Equipment

- Steel grille
- ON/OFF switch
- Hot gas defrost system
- Four reinforced rotary wheels
- Polymer mesh air filter
- Condensate pump
- Steel panels construction

The OASIS IP54 is an enhancement of the OASIS SD dehumidifier that has achieved compliance with the IP54 rating.

This high performance industrial dehumidifier has been engineered and certified for operation in dust-laden environments where the unit may be exposed to water sprays.

As a standard, the IP54 is equipped with an hour meter and a condensate pump. Sharing a similar cabinet style to the SD Range, this unit provides excellent strength and functional characteristics which is ideal for laboratory rooms and testing facilities.



Available Colours:

- Galvanised
- Custom



TECH SPEC

Product	IP54
Model	D270 IP54
Weight (kg)	29.5
Dimensions (cm)	60h x 38w x 37d
Power consumption (Watts)	400
Capacity (L/day) :	
10°C, 70% Relative Humidity	8.8
20°C, 60% Relative Humidity	9.5
27°C, 60% Relative Humidity	16.6
30°C, 80% Relative Humidity	27.2
Air Flow (Cubic meters/hr)	510
Refrigerant	R134a
Refrigerant Charge Weight	320
Power Supply	220-240V, 50/60Hz
Hot Gas Defrost System	Standard
Thermostat Defrost System	Option
Electronic Sensor defrost System	Option
Grille/Cabinet	Metal panels
Wheels	2 x 250
Handles	Side
Drainage System	Pump STD
Operating Control	ON/OFF
Air Filter	Yes

OASIS IRELAND

Bunree Industrial Estate,
Ballina, Co. Mayo, Ireland,
F26 D5R3.
+353 96 71222

OASIS POLAND

ul.Gutenbergga 20,
44-164, Gliwice, Poland
+48 32 332 65 01

www.oasis.ie

info@oasis.ie