



VERSACOOLER P8ACSLTMY.

Contactless + Manual, Refrigerated, Split-Level

Drinking Fountain

**For a hybrid activation, look no further:
Versacooler P8ACSLTMY is the
contactless + manual combo solution!**

Versacooler P8ACSLTMY delivers 60LPH of 10°C water at 21°C ambient. This split-level drinking fountain has two activation methods. One drinking fountain is activated via one of four push-pads, while the other includes an electronic sensor underneath the nose for a contactless (touch free) activation and a 30 second shut off timer.

Key Versacooler moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant CE directives (LVD , EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.



MODEL CODE	P8ACSLTMY
ACTIVATION	Contactless (Downward facing Infrared sensor) + Mechanical (Four push-pads)
SENSOR COVERAGE	Up to 5cm (approx.)
FILTRATION	Green Filter (optional), Built-in 100 micron strainer
DISINFECTION	Ultra Blu V (optional)
AUTO-OFF WATER FLOW	Yes (for contactless unit only)
DRAINAGE TYPE	Built in drain, Removable drip tray
EXTERIOR	Antimicrobial ABS Plastic, Antimicrobial copper touch points, Brushed Stainless Steel
CHASSIS	Heavy Duty Galvanised Steel
DIMENSIONS	480(H) x 448(W) x 473(D) mm (each)
NET WEIGHT	38 kg
POWER SUPPLY	220-240V, 50/60 Hz
COOLING PERFORMANCE	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)
FULL LOAD AMPS	2.2A
RATED WATTS	450 W
ENERGY SYSTEM	Refrigeration is on only when in use or if water temp increases during long period of standby.
COUNTRY OF ORIGIN	Mexico
CERTIFICATIONS	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)
WARRANTY	1 Year

